

| QTY. | PIPE SIZE NPS | A (IN) | PRESSURE* (PSI) | NOTES | EFP Part Number |
|------|------------------|--------|-----------------|-------|-----------------|
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |

*FOR SAFE WORKING PRESSURE ABOVE 70°F, MULTIPLY PRESSURE SHOWN AT 70°F TIMES CORRECTION FACTOR OF REQUIRED TEMP.

| TEMP °F | FACTOR |
|---------|--------|
| 70 | 1.0 |
| 150 | .95 |
| 200 | .91 |
| 250 | .88 |
| 300 | .85 |
| 350 | .81 |
| 400 | .78 |
| 450 | .77 |
| 500 | .77 |
| 600 | .76 |
| | |

NOTES:



NSF 372 - LEAD FREE: The wetted surface of this product contacted by water contains less than one quarter of one percent (0.25%) of lead by weight. Material complies with state codes and standards where applicable, requiring reduced lead content.

| REV. | DRAWN BY: AM | Date: 1/16/2019 | | | | | |
|----------------|---------------------------------------|--|--|--|--|--|--|
| ENGINEER | RED FLEXIBLE PRODUCTS, INC. | 5331 Quam Ave NE St. Michael, MN 55376 Phone: 763-201-2151 Fax: 763-201-2134 Email: sales@engineeredflex.com | | | | | |
| Customer: | | | | | | | |
| Project: | | | | | | | |
| Style: | Style: STAINLESS STEEL FLEX CONNECTOR | | | | | | |
| scale: None | DRAWING NUMBER: | | | | | | |