



QTY.	NOMINAL SIZE	A (IN)	PRESSURE* (PSI)	NOTES	MAX INTERMITTENT OFFSET FROM ϕ
	1/2"	6-1/2"	706		±1/8"
	3/4"	7"	577		±1/8"
	1"	8"	470		±1/8"
	1-1/4"	8-1/2"	361		±1/8"
	1-1/2"	9"	329		±1/8"
	2"	10-1/2"	317		±1/8"
	2-1/2"	12"	272		±1/8"
	3"	12"	211		±1/8"



*FOR SAFE WORKING PRESSURE ABOVE 70°F, MULTIPLY PRESSURE SHOWN AT 70°F TIMES CORRECTION FACTOR OF REQUIRED TEMP.

TEMP °F	FACTOR
70	1.0
150	.92
200	.89
250	.86
300	.83
350	.81
400	.78
450	.75
500	-
600	-

NOTES:

NSF 372 - LEAD FREE: The wetted surface of this product contacted by water contains less than one quarter of one percent (0.25%) of lead by weight. Material complies with state codes and standards where applicable, requiring reduced lead content.

REV. DRAWN BY: AM Date: 12/11/2018



5331 Quam Ave NE
 St. Michael, MN 55376
 Phone: 763-201-2151
 Fax: 763-201-2134
 Email: sales@engineeredflex.com

Customer:	
Project:	
Style:	BRONZE FLEX CONNECTOR
SCALE:	DRAWING NUMBER:
NONE	