



QTY.	NOMINAL SIZE	A (IN)	PRESSURE* (PSI)	NOTES	MAX INTERMITTENT OFFSET FROM ϕ
	1/2"	6-1/2"	1075		±1/8"
	3/4"	7"	792		±1/8"
	1"	8"	571		±1/8"
	1-1/4"	8-1/2"	531		±1/8"
	1-1/2"	9"	472		±1/8"
	2"	10-1/2"	516		±1/8"
	2-1/2"	12"	387		±1/8"
	3"	12"	316		±1/8"



*FOR SAFE WORKING PRESSURE ABOVE 70°F, MULTIPLY PRESSURE SHOWN AT 70°F TIMES CORRECTION FACTOR OF REQUIRED TEMP.

TEMP °F	FACTOR
70	1.0
150	.92
200	.89
250	.86
300	.83
350	.81
400	.78
450	.75
500	-
600	-

NOTES:

NSF 372 - LEAD FREE: The wetted surface of this product contacted by water contains less than one quarter of one percent (0.25%) of lead by weight. Material complies with state codes and standards where applicable, requiring reduced lead content.

REV.	DRAWN BY: AM	Date: 2/1/2019
		5331 Quam Ave NE St. Michael, MN 55376 Phone: 763-201-2151 Fax: 763-201-2134 Email: sales@engineeredflex.com
Customer:		
Project:		
Style: STAINLESS FLEX CONNECTOR W/SWEAT ENDS		
SCALE: NONE	DRAWING NUMBER:	