Spider Spacers Center **Guide Hardware:** Pipe In Housing And Are_ Material: Carbon Steel Sized To Allow Insulation Finish: One Coat of Paint To Be Packed Around Pipe For Copper Tube Clamps Use Dieletric Spacers G C-Movement -Feet Can Be Bolted Or Welded To Structure В Split Housing For_ Easy Installation F

Provides Lateral Stability To The Pipe To Prevent "Bowing". Guides Are Not Designed To Support The Weight Of The Pipe.

D

— E

Size	Ins	Model	Α	В	С	D	E	F	G	Movement	Weight
1/2"	4''	PG 004-410-4	6-1/4"	11-5/8"	12-1/8"	7''	5/8''	2-3/4"	4''	4''	17 lbs
3/4"	4''	PG 006-410-4	6-1/4"	11-5/8"	12-1/8"	7-1/8"	5/8''	2-3/4"	4''	4''	17 lbs
1"	4''	PG 010-410-4	6-1/4"	11-5/8"	12-1/8"	7-1/8"	5/8''	2-3/4"	4''	4''	17 lbs
1-1/4"	4''	PG 012-410-4	6-1/4"	11-5/8"	12-1/8"	7-1/8"	5/8''	2-3/4"	4''	4''	17 lbs
1-1/2"	4''	PG 014-410-4	6-1/4"	11-5/8"	12-1/8"	7-1/8"	5/8''	2-3/4"	4''	4''	17 lbs
2"	4''	PG 020-412-4	7"	13-3/8"	14-1/8"	8-3/8"	5/8''	2-3/4"	4''	4''	20 lbs
2-1/2"	4''	PG 024-412-4	7"	13-3/8"	14-1/8"	8-3/8"	5/8''	2-3/4"	4''	4''	20 lbs
3"	4''	PG 030-412-4	7"	13-3/8"	14-1/8"	8-3/8"	5/8"	2-3/4"	4''	4''	20 lbs
4''	4''	PG 040-414-6	7-7/8"	15-1/8"	16-1/8"	9-7/8"	3/4"	4''	6''	6''	40 lbs
5''	4''	PG 050-416-6	8-7/8"	17''	18-1/8"	10-7/8"	3/4"	4''	6''	6''	48 lbs
6"	4''	PG 060-416-6	8-7/8"	17''	18-1/8"	10-7/8"	3/4"	4''	6''	6''	48 lbs
8"	4''	PG 080-418-6	9-3/4"	18-3/4"	20-1/8"	11-7/8"	3/4"	4''	6''	6''	54 lbs
10''	4''	PG 100-420-6	10-7/8"	21"	22-1/8"	11-3/4"	3/4"	4''	6"	6''	61 lbs
12"	4"	PG 120-422-8	12-1/8"	23-1/8"	24-1/8"	14-1/2"	7/8''	6''	8"	8''	89 lbs
14"	4''	PG 140-424-8	13"	25''	26-1/8"	15-1/2"	7/8''	6''	8"	8''	102 lbs
16"	4''	PG 160-426-8	14-3/4"	27-3/4"	28-1/8"	17-1/8"	1-1/8"	6''	8"	8''	110 lbs
18''	4''	PG 180-428-8	15-1/2"	29-1/2"	30-1/8"	18-1/2"	1-1/8"	6"	8''	8''	135 lbs
20''	4"	PG 200-330-8	16-1/2"	31-1/2"	32-1/8	19-1/4"	1-1/8"	6"	8''	8''	150 lbs

*Extended Spider Guides Are Available, **Contact Engineered Flexible Products For Options**.

CUSTOMER:

PROJECT:_____

REV.	DRAWN BY: CL	Date: 1/18/2021				
-	ERED FLEXIBLE PRODUCTS, INC.	5331 Quam Ave NE St. Michael, MN 55376 Phone: 763-201-2151 Fax: 763-201-2134 Email: sales@engineeredflex.com				
Style:	GUIDES FOR LATION					
scale: NONE	DRAWING NUMBER:					