



QTY	PART NUMBER	PIPE SIZE	OAL	PRESSURE RATING (PSI)*	WEIGHT (LBS)	NOTES	LATERAL OFFSET
	PCS0200FLG	2"	9"	516	9		± 1/8"
	PCS0250FLG	2-1/2"	9"	387	13		± 1/8"
	PCS0300FLG	3"	9"	316	14		± 1/8"
	PCS0400FLG	4"	9"	232	18		± 1/8"
	PCS0500FLG	5"	11"	191	25		± 1/8"
	PCS0600FLG	6"	11"	165	28		± 1/8"
	PCS0800FLG	8"	12"	234	52		± 1/8"
	PCS1000FLG	10"	13"	230	75		± 1/8"
	PCS1200FLG	12"	14"	161	105		± 1/8"
	PCS1400FLG	14"	14"	150	115		± 1/8"
	PCS1600FLG	16"	14"	110	145		± 1/8"

**Safety factor is 4:1      Burst pressure is 4x rated working pressure**

**\*FOR SAFE WORKING PRESSURE ABOVE 70°F,  
MULTIPLY PRESSURE SHOWN AT 70°F TIMES  
CORRECTION FACTOR OF REQUIRED TEMP.**

TEMP °F	FACTOR
70	1.0
150	.95
200	.91
250	.88
300	.85
350	.81
400	.78
450	.77
500	.77
600	.76

**NOTES: NSF/ANSI 372, NSF/ANSI 61 ANNEX G COMPLIANT**  
 The wetted surface of this product contacted by water contains less than one quarter of one percent (0.25%) of lead by weight.  
 Material complies with state codes and standards where applicable, requiring reduced lead content.

REV.	DRAWN BY: BE	Date:
 <b>ENGINEERED FLEXIBLE PRODUCTS, INC.</b> <i>Connections when Motion Matters</i>		
Customer:		
Project:		
PCS Series Pump Connector - Flanged		
SCALE: NONE	DRAWING NUMBER:	