



QTY	PART NUMBER	PIPE SIZE	OAL	PRESSURE RATING (PSI)*	WEIGHT (LBS)	NOTES	LATERAL OFFSET
	PCS0050MMT	1/2"	6-1/2	1075	0.5		± 1/8"
	PCS0075MMT	3/4"	7	792	0.75		± 1/8"
	PCS0100MMT	1"	8	571	1.25		± 1/8"
	PCS0125MMT	1-1/4"	8-1/2	531	2		± 1/8"
	PCS0150MMT	1-1/2"	9	472	2.5		± 1/8"
	PCS0200MMT	2"	10-1/2	516	3		± 1/8"
	PCS0250MMT	2-1/2"	12	387	4.5		± 1/8"

\*FOR SAFE WORKING PRESSURE ABOVE 70°F,  
MULTIPLY PRESSURE SHOWN AT 70°F TIMES  
CORRECTION FACTOR OF REQUIRED TEMP.

TEMP °F	FACTOR
70	1.0
150	.95
200	.91
250	.88
300	.85
350	.81
400	.78
450	.77
500	.77
600	.76

**NOTES: NSF/ANSI 372, NSF/ANSI 61 ANNEX G COMPLIANT**  
The wetted surface of this product contacted by water contains less than one quarter of one percent (0.25%) of lead by weight.  
Material complies with state codes and standards where applicable, requiring reduced lead content.

REV.	DRAWN BY: CL	Date: 7/27/2023
 <b>ENGINEERED FLEXIBLE PRODUCTS, INC.</b> <i>Connections when Motion Matters</i>		
Customer:		
Project:		
PCS Series Pump Connector - Male NPT's		
SCALE: NONE	DRAWING NUMBER:	